liyondelibaseli	These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable		
	DVDOL VOIC CAC		DOO (UN#4000)
PRODUCT Material Characteristic and			PGO - (UN#1993)
material orial acteristic and	See Product SDS		
DOT SPECIFICATION	MC 307, DOT 407 (STAINLESS STEEL TRAILER)		
INSULATION	REQUIRED		
HEATING CAPABILITIES	REQUIRED		
GASKET MATERIAL	ROPE TEFLON, VIRGIN TEFON, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A LEAK TIGHT SEAL UPON COMPLETION OF LOADING. DOME-LID AND ALL OPENING MUST HAVE A SEAL POINT		
CONNECTIONS/FITTINGS	ALL MUST BE STAINLESS STEEL, W/DUST CAPS W/SEAL PONTS ON ALL OUTLETS OF THE TRAILER, CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL		
LIQUID CONNECTION	3 "MALE KAMVALOK, (DRY CONNECT), W/DUST CAP - BOTTOM REAR LOADER, (CENTER LOADER WILL REQUIRE APPROVAL). NOTE: CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS. MUST HAVE SEAL POINTS		
VAPOR CONNECTION	2" MALE KAMVALOK (DRY CONNECT), W/DUST CAP, WITH PIPING TO GRADE LEVEL (GLV), WITH 2" SS ISOLATION VALVE, (INLINE PRESSURE GAUGE @ GRADE LEVEL PREFERRED). 2" WITH DUST CAP, (MUST BE ABLE TO SEAL), STANDARD 3/4" TOP VAPOR CONNTECTION IS ACCEPTABLE		
NITROGEN PADDING	NITORGEN PURGED ARRIVAL)	, (TRAILER MUST	Γ HAVE A 5-7 PSIG PAD UPON
TANK CLEANLINESS	IF NOT DEDICATED A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. A CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. NOTE: IF TRAILER IS RE-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS IS REQUIRED TO INDICACTE THE SAME PRIOR PRODUCT.		
STRAPPING CHART	YES		
HOSES	FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING DOCUMENT.		
ADDITIONAL APPURTENANCES	NONE, CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL.		
OTHER	MUST HAVE SAP CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELLBASELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDANCE LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS		
PROHIBITED	NO ADDITIONAL PER PROHIBITED.	RSONNEL, UNLES	S TEAM DRIVERS, PETS ARE

Willie E. Phillips Revised Date: 10/31/2022 Print Date: 11/14/2022