lyondellbasell	These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading an Intermodal Container at a LyondellBasell site or a contracted 3PL location as applicable		
INTERMODAL CONTAINER SPECIFICATION			
PRODUCT	METHYL ETHYL KETON		
Material Characteristic and immediate hazard See Product SDS			
DOT SPECIFICATION	UN T-11, (STAINLESS STEEL CONTAINER). CONTAINER MUST BE APPROVED AND DESIGNATED BY LYB TO TRANSPORT METHYL ETHYL KETONE. DEDICATED CONTAINER IS NOT REQUIRED, BUT DEDICATED SERVICES CONTAINER WILL REQUIRE LYB WRITTEN PRE-APPOVAL PRIOR TO LOADING OR TRANSPORT OF METHYL ETHYL KETONE. SPECIAL NOTE : DATA PLATE INFORMATION MUST BE LEGIBLE AND CORRECTLY STAMPED. INSPECTION DOCUMENTATION MUST BE WITH DRIVER AS ADDITIONAL PROOF OF INSPECTION/TEST DATE VERIFICATION, TO HELP PREVENT EQUIPMENT REJECTION.		
INSULATION	REQUIRED		
HEATING CAPABILITIES	NOT REQUIRED		
GASKET MATERIAL	VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, VITON **DOME GASKET MUST GIVE A LEAK TIGHT SEAL UPON COMPLETION OF LOADING		
CONNECTIONS/FITTINGS	ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL.		
LIQUID CONNECTION	EXPORT SHIPMENT: BLIND FLANGE OR SOLID CLOSURE ON BOTTOM OUTLET IF CONTAINER IS TO BE LOAED ON RAIL OR VESSEL; BOTTOM OUTLET MUST HAVE A SOLID CLOSURE; DUST CAPS NOT ACCEPTABLE. <u>DOMESTIC SHIPMENT:</u> A FLANGED 3" MALE KAMVALOK (DRY CONNECT) W/DUST CAP - BOTTOM REAR LOADER . <u>BOTH SHIPMENT TYPES</u> : MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL. IF GL PIPING, (GROUND LEVEL), PIPING, IF NOT FRAME PROTECTED, SHOULD BE EQUIPPED WITH A SHEAR RING.		
VAPOR CONNECTION	1 1/2 - 2" INCH BALL VALVE WITH BULL PLUG, BULL PLUG MUST BE ATTACHED WITH CHAIN/CABLE AND VALVE MUST BE ABLE TO SEALED W/1/8" WIRE CABLE SEAL. VAPOR CLOSURES MUST ALIGN WITH SHIPMENT MODE REQUIREMENTS. NOTE : PROTECTIVE COVER FOR MAN-LID AND VAPOR CONNECTION MUST ALSO HAVE THE CAPABILITY TO SEALED. NOTE : IF GLV, (GROUND LEVEL VAPOR), PIPING, IF NOT FRAME PROTECTED, SHOULD BE EQUIPPED WITH A SHEAR RING. NO INLINE RUBBER HOSE ACCEPTABLE, ONLY SS FLEX HOSE OR HARD PIPING. THIS APPLIES FOR EXPORT OR DOMESTIC SHIPMENTS.		
NITROGEN PADDING	NITORGEN PURGE FOR DRYING, MOISTURE, FLAMMABLE ATMOSPHERE CONTROL. CLEAN CONTAINER MUST HAVE A 5-7 PSIG PAD UPON ARRIVAL AT LOADING FACILITY. RE- LOAD/RESUE CONTAINER MAY RETURN WITH LAST OFF-LOADING PRESSURE OR MININUM OF 5-7 PSIG.		
TANK CLEANLINESS	IF CONTAINER IS CLEANED, A CLEANING CERTIFICAE IS REQUIRED. CONTAINER MUST BE CLEAN, DRY, AND ODOR FREE. NOTE : IF CONTAINER IS RE-LOAD, THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF THAT THE LAST CONTAINED WAS LYONDELLBASELL MATERIAL.		
STRAPPING CHART REQUIRED	YES, NOTE: LEVEL GAUG	E/INDICATOR ALSO PREFERRED	
HOSES	· · /	RED AT LYONDELLBASELL LOADING FACILITIES. NOTE: HOSE(S) ARE CARRIER FOR EXPORT SHIPMENTS.	
ADDITIONAL APPURTENANCES OR REQUIREMENTS	NONE - NOTE : CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENING TO CONTAINER MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL. NOTE : PRODUCT LABELING IS REQUIRED WITH CONTAINER/(DRIVER), UPON ARRIVAL TO LOADING FACILITY.		
OTHER	MUST HAVE LYB CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELL OF ANY REQUESTED LIGHT LOADING, (PRIOR TO LOADING), DUE TO POTENTIAL EXCEEDING LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS		
PROHIBITED	PETS ARE PROHIBITED; A	ADDITIONAL PERSONNEL ONLY IF TEAM DRIVERS	