These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading an Intermodal Containe at a LyondellBasell site or a contracted 3PL location as applicable N-METHYL PYRROLIDONE (INDUSTRIAL) NMP Material Characteristic and immediate hazard See Product SDS UN T-11, (STAINLESS STEEL CONTAINER), CONTAINER MUST BE APPROVED AND DESIGNA BY LYB TO TRANSPORT N-METHYL PYRROLIDONE. DEDICATED CONTAINER IS NOT REQUIRE BUT DEDICATED SERVICES CONTAINER WILL REQUIRE LYB WRITTEN PRE-APPOVAL PRIOF LOADING OR TRANSPORT OF N-METHYL PYRROLIDONE. SPECIAL NOTE: DATA PLATE INFORMATION MUST BE LEGIBLE AND CORRECTLY STAMPED. INSPECTION DOCUMENTATION MUST BE WITH DRIVER AS ADDITIONAL PROOF OF INSPECTION/TEST DATE VERIFICATION, HELP PREVENT EQUIPMENT REJECTION. INSULATION PREFERRED BUT NOT REQUIRED VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, "DOME GASKET MUST GIVE A L TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/8"
Material Characteristic and immediate hazard UN T-11, (STAINLESS STEEL CONTAINER). CONTAINER MUST BE APPROVED AND DESIGNA' BY LYB TO TRANSPORT N-METHYL PYRROLIDONE. DEDICATED CONTAINER IS NOT REQUIR BUT DEDICATED SERVICES CONTAINER WILL REQUIRE LYB WRITTEN PRE-APPOVAL PRIOF LOADING OR TRANSPORT OF N-METHYL PYRROLIDONE. SPECIAL NOTE: DATA PLATE INFORMATION MUST BE LEGIBLE AND CORRECTLY STAMPED. INSPECTION DOCUMENTATI MUST BE WITH DRIVER AS ADDITIONAL PROOF OF INSPECTION/TEST DATE VERIFICATION, HELP PREVENT EQUIPMENT REJECTION. INSULATION PREFERRED BUT NOT REQUIRED VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A L TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH A 1/8"
Material Characteristic and immediate hazard UN T-11, (STAINLESS STEEL CONTAINER). CONTAINER MUST BE APPROVED AND DESIGNA' BY LYB TO TRANSPORT N-METHYL PYRROLIDONE. DEDICATED CONTAINER IS NOT REQUIR BUT DEDICATED SERVICES CONTAINER WILL REQUIRE LYB WRITTEN PRE-APPOVAL PRIOF LOADING OR TRANSPORT OF N-METHYL PYRROLIDONE. SPECIAL NOTE: DATA PLATE INFORMATION MUST BE LEGIBLE AND CORRECTLY STAMPED. INSPECTION DOCUMENTATI MUST BE WITH DRIVER AS ADDITIONAL PROOF OF INSPECTION/TEST DATE VERIFICATION, HELP PREVENT EQUIPMENT REJECTION. INSULATION PREFERRED BUT NOT REQUIRED VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A L TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH A 1/8"
UN T-11, (STAINLESS STEEL CONTAINER). CONTAINER MUST BE APPROVED AND DESIGNA BY LYB TO TRANSPORT N-METHYL PYRROLIDONE. DEDICATED CONTAINER IS NOT REQUIR BUT DEDICATED SERVICES CONTAINER WILL REQUIRE LYB WRITTEN PRE-APPOVAL PRIOF LOADING OR TRANSPORT OF N-METHYL PYRROLIDONE. SPECIAL NOTE: DATA PLATE INFORMATION MUST BE LEGIBLE AND CORRECTLY STAMPED. INSPECTION DOCUMENTATION MUST BE WITH DRIVER AS ADDITIONAL PROOF OF INSPECTION/TEST DATE VERIFICATION, HELP PREVENT EQUIPMENT REJECTION. INSULATION PREFERRED BUT NOT REQUIRED VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A L TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/8"
BY LYB TO TRANSPORT N-METHYL PYRROLIDONE. DEDICATED CONTAINER IS NOT REQUIF BUT DEDICATED SERVICES CONTAINER WILL REQUIRE LYB WRITTEN PRE-APPOVAL PRIOF LOADING OR TRANSPORT OF N-METHYL PYRROLIDONE. SPECIAL NOTE: DATA PLATE INFORMATION MUST BE LEGIBLE AND CORRECTLY STAMPED. INSPECTION DOCUMENTATION MUST BE WITH DRIVER AS ADDITIONAL PROOF OF INSPECTION/TEST DATE VERIFICATION, HELP PREVENT EQUIPMENT REJECTION. INSULATION PREFERRED BUT NOT REQUIRED HEATING CAPABILITIES PREFERRED NOT REQUIRED VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A L TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/8"
HEATING CAPABILITIES PREFERRED NOT REQUIRED VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A L TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/4
GASKET MATERIAL VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A L TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/1
GASKET MATERIAL VIRGIN TEFLON, TEFLON ROPE, TEFLON ENCAPSULATED, **DOME GASKET MUST GIVE A L TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/1
GASKET MATERIAL TIGHT SEAL UPON COMPLETION OF LOADING ALL MUST BE STAINLESS STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/1
CONTAINER (AS APPLICABLE). MUST BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL., DOME LID & VALVE COVER MUST CAPABLE OF BEING SEALED WITH 1/2"
WIRE CABLE SEAL.
EXPORT SHIPMENT: BLIND FLANGE OR SOLID CLOSURE ON BOTTOM OUTLET IF CONTAINE IS TO BE LOAED ON RAIL OR VESSEL; BOTTOM OUTLET MUST HAVE A SOLID CLOSURE; DL CAPS NOT ACCEPTABLE. DOMESTIC SHIPMENT: A FLANGED 3" MALE CAMLOCK (QUICK CONNECT) W/DUST CAP - BOTTOM REAR LOADER. BOTH SHIPMENT TYPES: MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL. IF GL PIPING, (GROUND LEVE) PIPING, IF NOT FRAME PROTECTED, SHOULD BE EQUIPPED WITH A SHEAR RING.
1 1/2 - 2" INCH BALL VALVE WITH BULL PLUG, BULL PLUG MUST BE ATTACHED WITH CHAIN/CABLE AND VALVE MUST BE ABLE TO SEALED W/1/8" WIRE CABLE SEAL. VAPOR CLOSURES MUST ALIGN WITH SHIPMENT MODE REQUIREMENTS. NOTE: PROTECTIVE COV VAPOR CONNECTION FOR MAN-LID AND VAPOR CONNECTION MUST ALSO HAVE THE CAPABILITY TO SEALED. NOTE: IF GLV, (GROUND LEVEL VAPOR), PIPING, IF NOT FRAME PROTECTED, SHOULD BE EQUIPPED WITH A SHEAR RING. NO INLINE RUBBER HOSE ACCEPTABLE, ONLY SS FLEX HO OR HARD PIPING. THIS APPLIES FOR EXPORT OR DOMESTIC SHIPMENTS.
NITORGEN PURGE FOR DRYING, MOISTURE, COMBUSTIBLE ATMOSPHERE CONTROL. CLEAR CONTAINER MUST HAVE A 5-7 PSIG PAD UPON ARRIVAL AT LOADING FACILITY. RE- LOAD/RESUE CONTAINER MAY RETURN WITH LAST OFF-LOADING PRESSURE OR MININUM 5-7 PSIG.
IF CONTAINER IS CLEANED, A CLEANING CERTIFICAE IS REQUIRED. CONTAINER MUST BE CLEAN, DRY, AND ODOR FREE. NOTE: IF CONTAINER IS RE-LOAD, THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF THAT THE LAST CONTAINED WAS LYONDELLBASELL MATERIAL.
STRAPPING CHART REQUIRED YES, NOTE: LEVEL GAUGE/INDICATOR ALSO PREFERRED
HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. NOTE : HOSE(S) ANOT TRANSPORTED BY CARRIER FOR EXPORT SHIPMENTS.
ADDITIONAL APPURTENANCES OR REQUIREMENTS NONE - NOTE: CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENING TO CONTAIN MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL. NOTE: PRODUCT LABELING IS REQUIRED WITH CONTAINER/(DRIVER), UPON ARRIVAL TO LOADING FACILITY
MUST HAVE LYB CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULEI TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELL OF ANY REQUESTED LIGHT LOADING, (PRIOR TO LOADING), DUE TO POTENTIAL EXCEEDING LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS
PROHIBITED PETS ARE PROHIBITED; ADDITIONAL PERSONNEL ONLY IF TEAM DRIVERS

 Willie E. Phillips
 Revised Date: 08/23/2022
 PRINT: 11/8/2022